# Plug & play purifiers to turn any indoor space into a virus-free environment

# REINTAIR® & REINTAIR® WARRIOR












# REINTAIR® & REINTAIR® WARRIOR

## Plug & play purifiers to turn any indoor space into a virus-free environment

### **MAIN FUNCTION**

- REINTAIR® by Casals air purifiers are plug & play sets (no installation required) to convert any interior space into an environment free of contaminating particles and thus leave a much healthier air.
- It is designed to reduce the viral load of the rooms given the constant air purifications that it carries out.



- 2. Aside from a healthier work environment, our air purifiers reduce the need for cleaning by removing a large portion of the dust that is generated daily.
- 3. Double filtration stage with two **ABSOLUTE HEPA H14** filter packages and a Molecular filter that in a matter of hours will reduce a large number of particles in the air such as microorganisms, bacteria, viruses, molecules, etc.
- 4. Available version with **UV-C lamp and photocatalysis** to inert the particles captured by the filters.
- 5. Equipped with high efficiency and silent fans to guarantee low energy consumption.






### **APPLICATIONS**

- Designed for all kind of indoor spaces such as:
  - health sector
  - offices
  - hotels
  - homes
  - universities
  - colleges
- In short, for any public space where high-quality air purification is required since REINTAIR® purifiers are equipped with high-efficiency HEPA H14 filters.
- Designed to be **easily moved** in indoor spaces, which makes them the best solution for:
  - Ventilation of workstations.
  - The health sector (waiting rooms, corridors, rooms, field hospitals, common areas, clinics, pharmacies, etc.).
  - The tertiary and industrial sector (offices, hotels, universities, schools, public institutions, warehouses, living rooms in restaurants).
  - The residential sector (single-family flats and houses).









2











### **IMPORTANT**

The REINTAIR purification system ensures the reduction of viral load by retaining viruses and bacteria (including COVID-19 coronaviruses) that pass through its high efficiency HEPA 14 filters. 100% air purification cannot be guaranteed in a specific space as it depends on different factors such as: architectural distribution of its location, external air currents, minimum operating time, improper use of the unit, obstruction of air inlets, maintenance level of the unit and the state of your filters, etc.

### **MANUFACTURING FEATURES**

- High efficiency purification unit built in soundproof steel structure, galvanized for corrosion resistance.
- Equipped with electronic EC motor, and available two constructive sizes:

MODEL	EQUIPMENT	APPLICABLE SURFACE
REINTAIR® S EC	EC motor	Up to 300m <sup>3</sup> /h for indoor spaces up to 45m <sup>2</sup> .
REINTAIR® S WARRIOR EC	EC motor, UV-C lamp and photocatalysis.	
DEINITAID® L. E.C.	FC markets	11 to 600003/b for indeed on an account to 00002

REINTAIR® L EC	EC motor	Up to 600m³/h for indoor spaces up to 90m².
REINTAIR® L WARRIOR EC	EC motor, UV-C lamp and photocatalysis.	

### CHASIS:

- Soundproof 30mm extruded aluminum profile, nylon corners and pre lacquered steel sandwich panels, RAL 9006, class M0, with 25mm internal rockwool insulation class A1 (non combustible) and 90Kg/m3 density. Panels come with quick release fastening system for easy assembly and disassembly whenever required, whether for cleaning, maintenance or panel repositioning.
- **Filters** are located in the perforated side panels, with **knobs and fastening system**. This ease of access optimizes maintenance and filter replacement procedures. Filter replacement and manipulation of the REINTAIR® is recommended with the appropriate PPE's.
- REINTAIR® purifiers are equipped with **4 wheels** with brakes on the base for ease of mobility throughout the indoor spaces and a **handle** to pull the equipment with only one hand.

### FAN:

Equipped with high efficiency single inlet - backward impeller with self-cleaning system, made of polyamide, statically and dynamically balanced at the factory.

### FILTERS:

- Dual filtering stage at each end of the REINTAIR® comprised of 2x ISO Coarse 65% (G4) + 2x HEPA H14.
- 4 filters per purification unit.
- The ISO Coarse 65% pre-filters increase the life of the absolute filters HEPA H14.

### MOTORS:

Low consumption EC (electronically commutated) Technology exterior rotor motor. IP-44 protection and class B insulation. Standard voltage 230V 50Hz/60Hz.

### **CONTROL PANEL:**

- All REINTAIR® air purifiers are equipped with a master control panel located on one side of the structure.
- This control panel allows for control of the following parameters:
  - 1. On/Off of the air Purifier.
  - 2. Automatic function Autonomous.
  - 3. Flow adjustment, 0 being the lowest and 10 the highest.
  - 4. Schedule control for night mode optimization and thus favouring low energy consumption when the interior spaces are empty.
  - 5. Clogged filter alarm and maintenance indication.
  - 6. Only in REINTAIR® WARRIOR version: total management of the UV-C lamp and photocatalysis such as the daily and hourly timer, or turning the lamp and photocatalysis on and off.










CV012021-1





### REINTAIR® WARRIOR EC VERSIÓN

- All REINTAIR® WARRIOR EC purifiers have the same equipment as standard REINTAIR® EC, but they also have the PHOTOCATALYSIS-UVC
  TOWER by Casals installed, consisting of a UV-C ultraviolet light lamp and a photocatalysis system that allows destroying the particles
  previously captured by the filters.
- PHOTOCATALYSIS-UVC TOWER by Casals carries out a photocatalytic oxidation process that combines UVC irradiation with a substance (catalyst) titanium dioxide (TiO2) which results in a reaction that changes harmful contaminants (bacteria, viruses and volatile organic compounds or VOC's) into H<sub>2</sub>O, CO<sub>3</sub> and detritus.
- The air purification process of using photocatalytic oxidation works by using an existing air system that pulls air through the RE-INTAIR® which passes through the professionally installed ultraviolet light/ titanium dioxide chamber. As the malignant contaminant-filled ambient air circulates through these chamber the microbes are "attacked" by free hydroxyl radicals and super-oxide ions (created by UV light and titanium dioxide) breaking their cellular structure apart and destroying both the intracellular mass and DNA/ HNA chromosomes. The result is harmless water molecules, carbon dioxide and detritus.



### **OPERATING SCHEME**



4


CV012021-1





5

### **EXTERNAL DIMENSIONS**




CV012021-1






	REINTAIR® S	REINTAIR® L
Height with wheels (mm)	670	975
Width (mm)	412	412
Length (mm)	412	412
Total Weight (Kg)	30	50

### REINTAIR S 300



REINTAIR L 600



### **TECHNICAL DATA OF REINTAIR®**

	REINTAIR® S EC REINTAIR® S WARRIOR EC	REINTAIR® L EC REINTAIR® L WARRIOR EC	
Phase	Single phase	Single phase	
Rated voltage (V)	230	230	
Rated voltage range (V)	220-240	220-240	
Frequency (Hz)	50/60	50/60	
Max. R.P.M	3980	3600	
Rated I (A) 230V	0,40	0,70	
Rated Power (W)	34	78	
Rated airflow (m³/h)	300	600	
Sound dB(A) (at 6m)	41	44	
Surfaces up to (m²)	45	90	
Min. ambient temperature (°C)	-25	-25	
Max. ambient temperature (°C)	50	50	

Note: The REINTAIR purifiers are 100% speed adjustables.

### **TECHNICAL DATA OF FILTERS**

	EFFICIENCY	DIMENSIONS WxHxD (mm)	MEDIUM AREA (m²)	AIRFLOW/ PRESSURE DROP at 0,45 m/s (m³/h / Pa)*	Weight (Kg)
HEPA FILTER REINTAIR S	H14	305 x 305 x 66	2	151/175	1,9
HEPA FILTER REINTAIR L	H14	305 x 610 x 66	4,1	301/175	3,2
ISO COARSE 65% (G4) FILTER REINTAIR S	ISO COARSE 65%	287 x 287 x 24	0,2	700/70	0,2
ISO COARSE 65% (G4) FILTER REINTAIR L	ISO COARSE 65%	287 x 592 x 24	0,3	1500/70	0,2





CV012021-1 6



### **VORTICE GROUP COMPANIES**

### VORTICE S.P.A

Strada Cerca, 2 Frazione di Zoate 20067 Tribiano (Milan) Italy Tel. (+39) 02 906991 Fax (+39) 02 90699625 vortice.com

### VORTICE LIMITED

Beeches House-Eastern Avenue Burton upon Trent DE13 OBB United Kingdom Tel. (+44) 1283 492949 Fax (+44) 1283 544121 vortice.ltd.uk

### VORTICE INDUSTRIAL S.R.L.

Via B. Brugnoli 3, 37063 Isola della Scala (Verona) Italy Tel. (+39) 045 6631042 Fax (+39) 045 6631039 vorticeindustrial.com

### CASALS VENTILACIÓN AIR INDUSTRIAL S.L.

Ctra. Camprodon, s/n 17860 Sant Joan de les Abadesses (Girona) Spain Tel. (+34) 972720150 casals.com

### VORTICE LATAM S.A.

Bodega #6 Zona Franca Este Alajuela, Alajuela 20101 Costa Rica Tel. (+506) 2201 6934 vortice-latam.com

# VORTICE VENTILATION SYSTEM

(Changzhou) Co.LTD No. 388 West Huanghe Road Building 19, Changzhou Post Code: 213000 China Tel. (+86) 0519 88990150 Fax (+86) 0519 88990151 vortice-china.com

The descriptions and illustrations in this catalogue are intended to be indicative and not binding. Without prejudice to the essential characteristics of the products described and illustrated here, CASALS reserves the right to make, at any time and without notice, changes to parts, aesthetic details or supply of accessories to its products that are deemed to be appropriate for improvement or for any construction or commercial requirement.

This printout completely cancels and replaces all the previous ones

